

CIRCUIT AND METHOD FOR DRIVING DISPLAY


Patent number: JP2000206919
Publication date: 2000-07-28
Inventor: FUJIKURA KATSUYUKI; FURUHASHI NAOKI
Applicant: NEC CORP
Classification:
 - International: G09G3/20; G09G3/28
 - european:
Application number: JP19990002353 19990107
Priority number(s):

Report a data error here

Abstract of JP2000206919

PROBLEM TO BE SOLVED: To make it possible to improve an efficiency of energy recovery and reduce costs of a PDP system as a whole without requiring a 2nd power supply source by composing a recovery circuit, a switch means, and a detecting circuit.

SOLUTION: A recovery circuit 1 is comprised of an auto-transformer 2, 1st switches 3-1 to 3-j, a switch 5, a switch control circuit 4, a power capacity 8, an energy supply circuit 9, etc. A switch means 21 is connected across a 1st terminal AT1 of the auto-transformer 2 and capacitive data electrodes 23-1 to 23-i, and is provided with 2nd switches 22-1 to 22-i to change over to/ from open/close state according to the states of the driving voltages on the capacitive data electrodes 23-1 to 23-i. A detecting circuit 10 inputs information on the open/close states of the 2nd switches 22-1 to 22-i in the switch means 21, and sends the detection result to the switch control circuit 4. Based on the result, the switch control circuit 4 judges which switches to be made ON- state among the 1st switches 3-1 to 3-j.



Data supplied from the esp@cenet database - Patent Abstracts of Japan